

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
18 January 2001 (18.01.2001)

PCT

(10) International Publication Number  
**WO 01/04682 A1**

- (51) International Patent Classification<sup>7</sup>: **G02B 17/08**, 21/04
- (74) Agents: **SMYRSKI, Steven, W.** et al.; Pillsbury Madison & Sutro LLP, 725 South Figueroa Street, Los Angeles, CA 90017-5443 (US).
- (21) International Application Number: PCT/US00/17121
- (22) International Filing Date: 22 June 2000 (22.06.2000)
- (81) Designated States (*national*): JP, KR.
- (25) Filing Language: English
- (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
- (26) Publication Language: English
- (30) Priority Data:  
09/349,036 7 July 1999 (07.07.1999) US
- Published:**  
— With international search report.  
— Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.
- (71) Applicant: **KLA-TENCOR CORPORATION** [US/US];  
160 Rio Robles, San Jose, CA 95134 (US).
- (72) Inventors: **SHAFFER, David, R.**; 56 Lake Lane, Fairfield, CT 06430 (US). **CHUANG, Yung-Ho**; 10678 Farallone Drive, Cupertino, CA 95014 (US). **ARMSTRONG, J., Joseph**; 729 Folsom Circle, Milpitas, CA 95035 (US).
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: BROAD BAND ULTRAVIOLET CATADIOPTRIC IMAGING SYSTEM



(57) Abstract: A design for inspecting specimens, such as photomasks, for unwanted particles and features such as pattern defects is provided. The system provides no central obscuration, an external pupil for aperturing and Fourier filtering, and relatively relaxed manufacturing tolerances, and is suited for both broad-band bright-field and laser dark field imaging and inspection at wavelengths below 365 nm. In many instances, the lenses used may be fashioned or fabricated using a single material. Multiple embodiments of the objective lensing arrangement are disclosed, all including at least one small fold mirror and a Mangin mirror. The system is implemented off axis such that the returning second image is displaced laterally from the first image so that the lateral separation permits optical receipt and manipulation of each image separately. The objective designs presented have the optical axis of the Mangin mirror image relay at ninety degrees to the optical axis defined by the focusing lenses, or an in-line or straight objective having one ninety degree bend of light rays.

## BROAD BAND ULTRAVIOLET CATADIOPTRIC IMAGING SYSTEM

This application is a continuation in part of United States Patent Application 09/046,814, entitled "High NA System for Multiple Mode Imaging," filed on March 24, 1998, which is a continuation in part of co-pending United States Patent Application 08/908,247, entitled "Ultra-Broadband UV Microscope Imaging System with Wide Range Zoom Capability," filed on August 7, 1997, which is a continuation in part of United States Patent Application 08/681,528, entitled "Broad Spectrum Ultraviolet Catadioptric Imaging System," filed on July 22, 1996, all of which are hereby incorporated by reference.

10 BACKGROUND OF THE INVENTIONField of the Invention

The present invention relates generally to the field of optical imaging and more particularly to catadioptric optical systems used for bright-field and dark-field imaging applications.

15 Description of the Related Art

Many optical and electronic systems exist to inspect object surfaces for defects such as those on a partially fabricated integrated circuit or a photomask. Defects may take the form of particles randomly localized on the surface of the circuit or photomask, as well as scratches, process variations, and so forth. Various imaging techniques used to perform surface inspection for such defects provide different advantages depending on the types of defects present.

Two well known imaging techniques for detecting defects are bright field imaging and dark field imaging. Bright field imaging is commonly used in microscope systems. The advantage of bright field imaging is the image produced is readily distinguishable. The size of image features accurately represents the size of object features multiplied by the magnification of the optical system. Bright field imaging can be more easily used with image comparison and processing algorithms for computerized object comparison, defect detection, and classification.

Dark field imaging has been successfully used to detect irregularities on object surfaces. The advantage of dark field imaging is that flat specular areas scatter very little light toward the detector, resulting in a dark image. Any surface features or objects

protruding above the object scatter light toward the detector. Thus, in inspecting objects like semiconductor wafers, dark field imaging produces an image of features, particles, or other irregularities on a dark background.

5 One advantage of dark field imaging is that it provides a large signal for small features that scatter light. This large signal allows dark field imaging to detect smaller object features and provide faster object inspections than bright field imaging. Another advantage is that Fourier filtering can be used to minimize repeating pattern signals and enhance the defect signal-to-noise ratio.

10 Many dark field imaging techniques have been developed to enhance the detection of different types of defects. These techniques consist of a specific illumination scheme and collection scheme such that the scattered and diffracted light collected from the object provides the best signal. Several optical systems have been developed that use different dark field imaging techniques including laser directional dark field, double dark field, central dark ground, and ring dark field.

15 When employing either bright field or dark field imaging it is often desirable to use short wavelength illumination in the 300-400 nm ultraviolet (UV) range, 200-300 nm deep ultraviolet (deep UV or DUV) range, or 100-200 nm vacuum ultraviolet (vacuum UV or VUV) range. For bright field imaging short wavelength illumination provides improved resolution allowing the detection of smaller object features. For dark field imaging short  
20 wavelength illumination provides greatly increased scattering signals that allow the detection of smaller objects, an increase in inspection speed, or a decrease in the illumination power requirements. In addition, both bright field and dark field imaging can take advantage of changes in material absorption and reflectivities at short wavelengths. The changes in absorption and reflectivity of different materials at short wavelengths can  
25 help to identify these different materials. Also, many materials have greatly increased absorption at wavelengths in the DUV and VUV. Increased absorption can help improve optical inspection of upper surfaces, such as in semiconductor wafer inspection, by minimizing reflections interference from underlying layers.

30 Optical systems supporting bright field and dark field imaging typically require correction over some finite spectral bandwidth or wavelength range. Correction is necessary because different wavelengths have different glass indexes, known as dispersion.

Conventional designs usually use two or three glass types to compensate for dispersive effects. Compensating for these dispersive effects is called color correction. Color correction in the UV, DUV, and VUV wavelength ranges is increasingly difficult. At shorter wavelengths, the glass dispersion greatly increases and is difficult to correct. In addition, at shorter wavelengths fewer and fewer glass materials may be used for correction.

At wavelengths shorter than 365 nm there are very few glass materials having high transmission. These materials typically include silica,  $\text{CaF}_2$ ,  $\text{MgF}_2$ , and  $\text{LiF}_2$ . Of these materials, silica is most desirable to use in high end optical systems. Silica is a hard glass with low thermal expansion, no birefringence, high UV damage threshold, and is not sensitive to humidity.  $\text{CaF}_2$ ,  $\text{MgF}_2$ , and  $\text{LiF}_2$  are soft glasses which are difficult to polish, have high thermal expansion, some birefringence, and can be sensitive to humidity. Of these fluoride glasses,  $\text{CaF}_2$  is the most desirable to use as an optical glass.

Minimizing the number of glass materials used in a UV, DUV or VUV optical system produces special challenges for correcting color aberrations. This is especially true in the VUV wavelength range where both silica and  $\text{CaF}_2$  are extremely dispersive. Even a narrow spectral bandwidth at very short wavelengths can require the correction of numerous distinct color aberrations. Some important color aberrations that need to be corrected may include primary and secondary axial color, primary and secondary lateral color, chromatic variation of spherical aberration, and chromatic variation of coma.

At a wavelength of 157 nm, for example,  $\text{CaF}_2$  is the only reasonable glass material that has high transmission and does not have severe problems with birefringence, water solubility, or mechanical softness. Standard color correction is not possible because no other glass material is available.

Another problem with currently available systems is that such systems provide a relatively short working distance between the optical system and the surface being inspected. Photomask inspection requires the working distance of the imaging system to be greater than approximately 6 millimeters due to the protective pellicle present on the photomask. A long working distance is also desirable in laser dark-field inspection environments. An imaging system having a long working distance makes it possible to directly illuminate the surface being inspected from outside the objective. Under typical

circumstances, a working distance greater than 4 millimeters presents generally desirable attributes, while a working distance greater than 8 millimeters is preferred.

Further, a high numerical aperture (NA) provides advantages for high resolution imaging and collecting as large a solid angle as possible. It is highly desirable to achieve  
5 numerical apertures of 0.8, which corresponds to collecting angles above the surface from normal to 53 degrees.

A further problem with currently available systems is that while some relatively high NA systems exist, the central returning rays may be obscured due to apertures and other optical components. Such a central obscuration blocks low frequency information from the  
10 image and is undesirable.

Additionally, some presently available systems include internal pupil planes. A system having an internal pupil plane is undesirable because it does not readily support aperturing, particularly variations in aperture shapes, and Fourier filtering.

Finally, some currently available systems have limited field sizes. A large field size  
15 is often important for area imaging and to allow high speed inspection such as for semiconductor wafers and photomasks. Field size is typically limited by aberrations such as lateral color and chromatic variation of aberrations. Aberration correction is especially difficult if combined with chromatic correction for a large spectral bandwidth, high NA, long working distances, no central obscuration, and an external pupil plane.

Two prior patents describe high NA catadioptric systems that can support this type  
20 of imaging. These patents are U.S. Patent 5,717,518 to Shafer et al. and U.S. Patent Application No. 09/046,814 to Chuang et al, both assigned to KLA-Tencor Corporation and hereby fully incorporated by reference.

U.S. Patent 5,717,518 describes an apparatus capable of high NA, ultra broad-band  
25 UV imaging. The '518 patent presents a 0.9 NA system for broad-band bright field and multiple wavelength dark-field imaging. The '518 system has a high degree of chromatic correction using a single glass material. Further correction is possible using two glass materials. The '518 system employs an achromatized field lens group to correct for secondary and higher order lateral color. This design has several limitations, including a  
30 limited working distance, central obscuration, internal pupil, and relatively tight

manufacturing tolerances. The primary method for laser dark-field illumination in this scheme is to direct a laser through a hole or aperture in the spherical mirror element. This type of illumination can be quite complicated to implement.

U.S. Patent Application No. 09/046,814 discloses an apparatus capable of  
5 combining ultra high NA, narrow-band UV imaging and multiple laser dark-field imaging techniques into a single optical system. The design is single wavelength and operates at numerical apertures up to 0.99. The '814 application is ideally suited for use in laser dark-field inspection, but has several limitations, including a relatively narrow working distance, a central obscuration, a narrow bandwidth, and relatively tight manufacturing tolerances.  
10 The system in the '814 application uses a similar technique to that shown in the '518 patent for laser dark-field illumination and generally has similar advantages and limitations.

Other specialized catadioptric optical systems have been developed for use in semiconductor lithography. These systems are designed to image a photomask at a reduced magnification onto a resist coated wafer. Two prior patents describe high NA catadioptric  
15 systems that can support this type of imaging, specifically U.S. Patent 5,052,763 to Singh et al. and European Patent Application number EP 0 736 789 A2 to Takahashi.

The '763 patent describes a catadioptric optical system capable of high NA imaging. This optical system is designed to create a substantially flat image field over the large areas required for semiconductor lithography. The design utilizes an input optical system having  
20 a curved field, a catadioptric relay system, and an output optical system to correct for the field curvature and some monochromatic aberrations. Limitations for the '763 design include a limited working distance, an internal pupil, a narrow bandwidth, an internal beamsplitter, and tight manufacturing tolerances.

The Takahashi European Patent Application presents a catadioptric optical system  
25 capable of high NA imaging. This optical system is designed to reduce the required diameter of the catadioptric mirror element for long distances to the wafer. The Takahashi design has an internal pupil, a narrow bandwidth using multiple glass materials, and tight manufacturing tolerances.

It is therefore desirable to provide a system for performing both bright field and dark  
30 field surface inspection having an objective which corrects image aberrations, chromatic

variation of image aberrations, and longitudinal (axial) color and lateral color, including residual (secondary and higher order) lateral color correction over a broad spectral range. Such a system should be relatively inexpensive and easy to operate in typical environments, provide a relatively long working distance, large field size, and have lenient tolerances. It is preferable to have such a system which operates at UV, DUV, or VUV wavelengths, a high numerical aperture, without central obscuration, and with an accessible pupil plane.

#### SUMMARY OF THE INVENTION

It is an object of the present invention to provide a system that is ideally suited to support both broad-band bright-field and laser dark field imaging and inspection.

It is another object of the present invention to provide a system having a high degree of chromatic correction using a minimum number of glass types, and even a single glass type.

It is a further object of the present invention to provide an apparatus that has a relatively long working distance between the optical system and the surface being inspected, a high numerical aperture, and no central obscuration. Such a system should have a working distance at least greater than 2 millimeters and preferably greater than 6 millimeters, with supporting numerical apertures as high as possible.

It is yet another object of the present invention to provide an inspection system having an external pupil plane to support aperturing and Fourier filtering.

It is still another object of the present invention to provide a system having relatively loose tolerances and which can be manufactured at a relatively reasonable cost.

These and other objects of the present invention are achieved by properly configuring the separate components of a catadioptric imaging system to interact with light in a precise and predetermined manner. The present invention is a catadioptric imaging method and apparatus for optical imaging and inspection. The design approach disclosed herein is ideally suited for both bright field and dark field imaging and inspection at wavelengths at or below 365 nm. In many instances, the lenses used in the system disclosed herein may be fashioned or fabricated using a single material, such as calcium fluoride or fused silica.

The first embodiment uses the catadioptric optical system as an apparatus for photomask inspection. This embodiment consists of illumination optics such as transmission illumination optics or reflected illumination optics, a long working distance catadioptric imaging objective, image forming optics, and a detector.

5 The second embodiment uses this optical system as an apparatus for laser dark field inspection. This apparatus consists of illumination optics, such as a laser illumination element, a long working distance catadioptric imaging objective, a Fourier filter or aperture at the external pupil plane, image forming optics, and a detector. Several additional  
10 embodiments describe the optical apparatus in the following detailed description. Two basic catadioptric objective design approaches are employed in these embodiments. Both approaches take advantage of multiple internal images for aberration correction and to produce a design with no central obscuration. The first design approach uses a reflective lens mirror element that is folded such that the optical axis is at an angle to the optical axis of the major refractive components. The second design approach uses a reflective lens  
15 mirror element that has its optical axis mostly coincident with the optical axis of the major refractive components. Each of these design approaches can correct for at least 1 nm of spectral bandwidth at 193 nm using a single glass material. The design can also correct for 0.5 nm of spectral bandwidth at 157 nm. Addition of a second glass material provides the ability to increase spectral bandwidth. For example, at 193 nm, the spectral bandwidth can  
20 be increased to greater than 10 nm using silica and CaF<sub>2</sub> glass.

The second design approach has the optical axis of a Mangin mirror coincident or nearly coincident with the optical axis of the refractive components. This design provides relatively relaxed manufacturing tolerances and increased design flexibility.

25 The image forming optics highly important in both the first and second embodiments. Two possible design options are presented for the image forming optics. These two options are a dual motion varifocal zoom and a single motion optically compensated zoom. Both zoom options provide a range of magnifications that would be useful in the first or second embodiments. Both of these zoom options can provide high quality images when combined with the catadioptric objective approaches described herein.

30 Several additional advantages are achieved with the current invention. First, the designs can be implemented using a single glass type for each of the lenses, thereby



facilitating production of an imaging system which utilizes the single best refractive material for broad band UV, DUV, or VUV applications.

Other significant advantages of the current invention include the ability to correct for primary, secondary, and higher order chromatic variations in focus, as well as  
5 correction for primary, secondary, and higher order lateral color, and corrections made for the chromatic variations of aberrations such as spherical, coma, and astigmatism.

An additional advantage of the current invention is the excellent performance with a broad bandwidth, long working distance, high NA, and a large flat field.

There has been outlined rather broadly the more important features of the invention  
10 in order that the detailed description thereof that follows may be better understood, and in order that the present contribution in the art may be better appreciated. These and other objects and advantages of the present invention will become apparent to those skilled in the art from the following detailed description of the invention and the accompanying drawings.

Those skilled in the art will appreciate that the conception on which this disclosure is based  
15 may readily be utilized as the basis for the designing of other arrangements for carrying out the several purposes of the invention. It is important therefore that this disclosure be regarded as including such equivalent arrangements as do not depart from the spirit and scope of the invention.

#### DESCRIPTION OF THE DRAWINGS

20 FIG. 1 illustrates a method of optical imaging and bright field and ring dark field inspection at wavelengths at or below 365 nm;

FIG. 2 illustrates a method of optical imaging and inspection using laser dark-field at wavelengths at or below 365 nm;

FIG. 3 is an example folded 0.7 NA catadioptric objective utilizing a single glass  
25 material;

FIG. 4 illustrates the effect of the lateral separation between rays transmitted to and received from the Mangin mirror;

FIG. 5 presents an embodiment of the design that provides narrow band aberration correction to give a 0.7 NA, long working distance, unobscured design using only fused silica;

FIG. 6 presents an embodiment of the invention having a folded 0.7 NA catadioptric objective using silica and calcium fluoride to further increase system bandwidth;

FIG. 7 presents an embodiment of the invention having an in-line or straight 0.7 NA catadioptric objective employing a single glass material;

FIG. 8 presents an embodiment of the invention optimized for a wavelength of 157 nm wherein the lenses shown are fashioned from calcium fluoride;

FIG. 9 presents an embodiment of the invention using two glass materials to increase the correction bandwidth from 193 to 203 nm;

FIG. 10 presents an embodiment of the image forming optics using a varifocal two motion zoom;

FIG. 11 presents three different magnifications possible with the varifocal zoom;

FIG. 12 presents an embodiment of the image forming optics using a single motion optically compensated zoom; and

FIG. 13 presents three different magnifications possible with the optically compensated zoom.

#### DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 illustrates a first embodiment of the current invention, including a method of bright field or ring dark field inspection. This method is particularly suited for photomask or wafer inspection, and consists of illumination optics such as transmission illumination source 101 or reflected illumination source 105, a long working distance catadioptric imaging objective 102, image forming optics 103, and a detector 104. For wafer inspection, only reflected light illumination is required. The design of the long working distance catadioptric objective and the image forming optics are enabling technologies for photomask inspection at wavelengths at or below 365 nm. Optical designs that support this photomask inspection method using a single material and two materials will be disclosed in

embodiments 3-10. The optics and detector are all carefully designed and optimized for the wavelength and spectral bandwidth of the illumination, as will be detailed below.

Different illumination sources may be employed in this design and incorporated in the transmitted light illumination 101 and reflected light illumination 105 and with the designs of embodiments 3-10 and with respect to FIGS. 3-13. These light sources include but are not limited to lasers and lamps. Many different lasers are available at wavelengths at or below 365 nm including argon (364, 351, 333, 275 nm), frequency converted lasers (351 nm, 266 nm, 213 nm), helium cadmium (325 nm), xenon chloride excimer (308 nm), krypton fluoride excimer (248 nm), argon fluoride excimer (193 nm), fluorine (157 nm), and argon excimer (126 nm). In addition, different wavelength lasers are possible using frequency mixing techniques. Many different lamp sources are available including mercury xenon (365-220 nm), cadmium lamp (210-220 nm), deuterium (150-190 nm), as well as various excimer lamps. These sources can have very different spectral bandwidths. For example, an unnarrowed excimer laser, a lamp having a bandpass filter, or a frequency converted laser can each produce light having a 1 nm bandwidth or less. An unfiltered lamp or lamp with a larger bandpass filter, such as an arc lamp, excimer lamp, or a deuterium lamp, are also possible sources having bandwidth greater than 1 nm. Relatively few light sources are available at 193 nm and 157 nm wavelengths. Of these light sources, excimer lasers have the brightness required to support high speed photomask inspection.

The illumination used in the embodiment illustrated in FIG. 1 can be either transmitted light, shown as transmitted illumination source 101, reflected light, shown as reflected illumination source 105, or both. The illumination may also be in the form of a ring such as required for ring dark field imaging. For example, this ring illumination can be obtained by placing a ring shaped aperture at or near a pupil plane located in the illumination system. This aperture blocks small illumination angles near the optical axis of the pupil and allow higher illumination angles away from the optical axis of the pupil. This ring should preferably be matched to a similar ring in the catadioptric objective or image forming optics such that all the rays from the illumination ring are blocked in the image.

Note that in the case of the reflected illumination source that the system employs beamsplitter/reflector 106. In the case of transmitted illumination using transmitted illumination source 101, photomask 107 is disposed between transmitted illumination source 101 and objective 102.

The illumination system for transmitted light preferably employs a condenser objective. The purpose of the condenser objective is to illuminate a region nominally the same size as the imaging region on a wafer or photomask. As the condenser objective is used only for illumination, it does not require high optical quality. Such an objective can be  
5 a reduced performance version of the catadioptric objectives presented in this invention or a simple all refractive design. Such designs are achievable by those skilled in the art when presented with this disclosure. The illumination for reflected light uses a beamsplitter and is implemented as in a standard microscope.

The long working distance imaging objective 102 includes the lensing arrangements  
10 described in embodiments 3 through 8 and illustrated in FIGS. 3-13. For photomask inspection, these designs should fulfill certain basic requirements. The objective working distance should be greater than 6 mm so as not to interfere with a pellicle that protects the reticle. The objective should also preferably be well corrected for aberrations over the bandwidth of the illumination source. Many of the available illumination sources have a  
15 bandwidth greater than the 1-2 nm bandwidth obtained from a standard type of single material all refractive objective design. An example of this is an unnarrowed excimer laser that typically has a spectral bandwidth around 1 nm. The catadioptric designs in embodiments 3-8 address this problem.

The objective should also have the ability to image over a relatively large field.  
20 Large fields and high data acquisition rates are essential to make inspecting the photomask as fast as possible.

The image forming optics 103 are corrected over the spectral bandwidth of the illumination source and the catadioptric imaging objective. The image forming optics 103 are also capable of various magnifications required in a photomask inspection environment.  
25 The image forming optics 103 and the catadioptric objective 102 may each and together be fully corrected for aberrations. Such aberration correction permits testing the image forming optics 103 and the catadioptric objective 102 as separate units. Alternately, aberration correction may be shared between the catadioptric objective 102 and the image forming optics 103. In general the optical design for shared aberration correction can be  
30 simpler to fabricate, but testing of the image forming optics and the catadioptric objective can be more complex.

The image forming optics or catadioptric objective can alternately contain a ring aperture at or near a pupil plane such as required for ring dark field imaging. This aperture

should block all direct illumination light from reaching the detector, corresponding to a similar aperture in the illumination. Thus the illumination aperture would be a transmissive ring and the imaging aperture would be a corresponding opaque ring.

Combinations of bright field imaging and ring dark field imaging are also possible.

5 Bright field and dark field may be combined on separate detectors or on the same detector at the same times or in an alternate fashion, as is generally known in the art. When bright field and dark field imaging is performed on the same detector at the same time, the relative intensity and phase of the light energy can be modified by suitable apertures in the illumination and imaging.

10 The detector 104 is preferably a high speed detector capable of the high data rates used for inspection systems. Detector 104 can be a single point diode type detector or an area type detector such as a CCD or a CCD operating in the Time Delay and Integration (TDI) mode. Ideally, this detector should have a high quantum efficiency, low noise, and a good Modulation Transfer Function (MTF). Back thinned CCD sensors are particularly  
15 well suited for this purpose.

The second embodiment is a method for laser dark-field inspection at or below 365 nm, and is illustrated in FIG. 2. The embodiment illustrated in FIG. 2 is especially suited for wafer and photomask inspection. The apparatus of FIG. 2 consists of illumination optics, such as laser illumination element 201, a long working distance catadioptric imaging  
20 objective 202, a Fourier filter or aperture 203 at the external pupil plane, image forming optics 204, and a detector 205. Catadioptric imaging designs using a single material in the configuration of FIG. 2 preferably use an illumination source having a 1 nm or less bandwidth. Catadioptric imaging designs using two glass materials are achievable when using an illumination source with greater than 1 nm bandwidth.

25 The types of illumination that can be used for this system are similar to those used in the first embodiment for bright field and ring dark field inspection. The preferred energy or light source is a laser due to its directionality and brightness. One method or apparatus for laser-dark field illumination of a semiconductor specimen is direct illumination of the specimen from outside the objective. In such an arrangement, only light scattered from the  
30 specimen is collected by the catadioptric objective. The specularly reflected beam is beyond the numerical aperture of the objective and is not collected.

Again, the long working distance imaging objective 202 is described in embodiments 3 through 8 and with respect to FIGS. 3-13. For laser dark field inspection,

these designs fulfill certain basic requirements. The long working distance offered by the designs of FIGS. 3-13 simplifies delivering laser energy to the wafer in the semiconductor specimen environment from outside the objective without interfering with the operation of the imaging system. The objective is preferably also well corrected for aberrations over the bandwidth of the illumination source 201. Many of the available illumination sources have a bandwidth that is greater than the 1-2 nm bandwidth obtained from a standard type of single material all refractive objective design. An example of this is an unnarrowed excimer laser that typically has a spectral bandwidth around 1 nm. The catadioptric designs in embodiments 3-8 address this problem. The objective 202 images over a large field, as large fields and high data acquisition rates provide for rapid wafer or photomask inspection.

The objective also preferably has an easily accessible pupil plane to support Fourier filtering or aperturing, such as by the Fourier filter or aperture 203. Fourier filtering can reduce the noise caused by repeating patterns on the wafer, thereby permitting smaller random defects to be more readily detected.

The image forming optics 204 are preferably corrected over the spectral bandwidth of the illumination and the catadioptric imaging objective 202. The image forming optics 204 also preferably support the various magnifications required by a dark field inspection system. One implementation of the image forming optics 204 is to have them and the catadioptric objective 202 each fully corrected for aberrations. Such a system allows simplified testing of image forming optics 204 and the catadioptric objective 202 as separate units. An alternate technique is sharing aberration correction between the catadioptric objective 202 and the image forming optics 204. Such an approach can be mechanically or optically simpler, but can complicate image forming optics and catadioptric objective testing.

Again, as in the first embodiment shown in FIG. 1, the detector 205 of FIG. 2 is preferably a high speed detector capable of the high data rates used for an inspection system. Detector 205 can be a single point diode type detector or an area type detector such as a CCD or a CCD operating in the TDI mode. Ideally, this detector should have a high quantum efficiency, low noise, and a good MTF. Such detectors are generally known to by those skilled in the art.

The design of FIGS. 1 and 2 can support bright field, laser directional dark field, ring dark field, and simultaneous bright-field and dark-field schemes, where each of these schemes can be achieved in the presence of UV, DUV, and VUV wavelengths. The

opaqueness of CMP layers in the deep UV and VUV ranges makes a system using this objective ideally suited to finding surface defects and microscratches on semiconductor wafers.

The catadioptric optical apparatus presented to support bright field and dark field  
5 imaging and inspection are also ideal for use in a variety of other applications. The design can be easily optimized by someone skilled in the art for wavelengths from the visible range to the deep UV range and to the vacuum UV range. Longer wavelengths can be optimized for larger bandwidths because the glass dispersion is less. For example, bandwidths of greater than 140 nm are possible with a two material design and a center wavelength of 300  
10 nm. The light energy can include shorter wavelengths and the design permits use of multiple wavelengths. For semiconductor inspection, the designs presented can support bright field, laser directional dark field, ring dark field, and simultaneous bright-field and dark-field schemes. The optical designs presented are also ideally suited for use as a lithography lens or for lithography simulation, a research tool for micro-electronic  
15 development, florescence measurements, or in biology where a long working distance is required for sample clearance. Due to the ability of this objective to provide applications in the presence of extremely varied light wavelengths and spectral bandwidths, the designs in FIGs. 1 and 2 are well suited for florescence measurements.

FIG. 3 illustrates a third embodiment of the present invention. This third  
20 embodiment is simple example of a folded 0.7 NA catadioptric objective 300 utilizing a single glass material, provided herein to explain the aberration correction and objective functionality. As with the other figures discussed herein, FIG. 3 includes a line in the upper left corner indicating a reference measurement of the size, in millimeters, of the associated line.

25 Also, as in other figures discussed herein, light is shown entering from the left side of FIG. 3 from an energy source 3000 (not shown).

The energy from the energy source 3000 is focused by a group of positive and negative lenses 301 arranged in either a telephoto or inverse telephoto configuration. The positive lens may be either in the front or in the back of the arrangement, where front and  
30 back are relative terms with respect to the energy source. Here negative lens 302 is in front of positive lens 303, where negative lens 302 and positive lens 303 form the group of

positive and negative lenses 301. A positive field lens 304 is located somewhat in front of the focus for lens group 301. Very close to the small image formed is located a relatively small pair of flat fold mirrors 305 arranged in a V-shape. The first small flat mirror 305a reflects the light at 90 degrees to the optical axis. Some other angular amount may be used depending on the application desired while still within the scope of the present invention.

The diverging light then proceeds to the Mangin mirror 306 located at the bottom of FIG. 3. A Mangin mirror is a lens/mirror element that is refractive and has a reflective back surface. The Mangin mirror 306 re-images the first image onto the second small flat folding mirror 305b, at substantially unit magnification. The system is implemented far enough off axis such that the returning second image is displaced laterally enough from the first image so that the lateral separation permits optical manipulation of each separate image. The amount of lateral separation allows the second small flat mirror 305b to fold the light path back onto the original optical axis. This effect is illustrated in FIG. 4.

According to FIG. 4, the input rays in the field of the substantially unit magnification Mangin mirror relay are on one side of the field and the output rays are on the opposite side. From FIG. 3, the second small fold mirror 305b is followed by a second field lens 307. From there the light proceeds up to the final focusing lenses 308 discussed below. This final focusing lens group 308 provides a relatively long working distance to the surface of the specimen, such as the photomask or semiconductor wafer.

If the two field lenses were not present in the design of FIG. 3, this design would constitute an application of the Schupmann type design using a Mangin mirror. The Mangin mirror would provide the means by which the virtual image of the Schupmann system would be turned into a real image, just as shown in previously known systems. This new configuration provides two significant advantages over the previous designs: lack of obscuration and a relatively long working distance. Both advantages result from the novel arrangement of the small fold mirrors 305, the substantially unit magnification Mangin mirror 306, and the presence of the two intermediate images in the system.

The small fold mirrors 305 can be implemented in a variety of ways. Objective designs can be optimized where these fold mirrors are on the sides of the field lenses opposite to the internal images. Objective designs can also be optimized where the small fold mirrors are on the side of the internal image closest to the Mangin mirror. Also, a



prism or prisms can be used for the reflective surfaces. A reflective coating can be added to one or more of the prism surfaces, such that the two prisms can be used as reflective mirrors. Alternately, one prism can have two surfaces coated and serve as both reflective surfaces. This is advantageous because a highly accurate angle can be polished on the prism to define the angle of the optical axis. The prisms can also be used in total internal reflection mode. This is advantageous when high efficiency optical coatings are difficult, such as for short wavelengths or broad spectral bandwidths. In this mode, the hypotenuse of a near 90 degree prism is used in total internal reflection, replacing a reflecting surface. The surfaces of the prism that are near normal to the incoming and reflecting beams may be anti-reflection coated to improve transmission efficiency.

Addition of one field lens to the system, in either of the two locations where the design has its two field lenses, provides the ability to correct the design for either secondary axial color or primary lateral color. Primary axial color is corrected without field lenses by balancing the positive refractive power of the Mangin mirror element 306 with the positive power of the lenses, as in connection with the Schumpmann principle. Use of two field lenses 304 and 307 near the intermediate images provides for correction of both secondary axial color and primary lateral color. The result is a design with a fairly broad spectral range having good axial color correction, but one that is limited by secondary axial color. Correction of the secondary lateral color can be accomplished by balancing the secondary color between the first half of the system with the second half of the system, where the first half of the system includes all lenses from the incoming energy source up to the reflective portion of the Mangin mirror 306, including lens group 301, field lens 304, first small fold mirror 305a, and Mangin mirror 306. This secondary lateral color balancing scheme works well due to the two intermediate images produced as in FIG. 4 and the two separate field lenses 304 and 307 present in the system. As in known systems, tertiary axial color is improved by moving the field lenses 304 and 307 a significant distance to one side of the intermediate images.

The present invention presented is a catadioptric system requiring a single refractive material, in conjunction with the particularly described arrangement of mirrors, to correct for chromatic aberrations. For a design intended for use in the presence of an energy source wavelength near 193 nm, the preferred lens material is silica. For a similar design intended for use in wavelengths near 157 nm, the preferred lens material is  $\text{CaF}_2$ . At 157 nm

wavelength, for example,  $\text{CaF}_2$  is preferred since it does not have severe problems with birefringence, water solubility, or mechanical softness. Further chromatic correction can also be achieved using two glass materials, but such an arrangement may require additional cost or present birefringence, water solubility, or mechanical softness drawbacks.

5 Special challenges are presented when correcting various color aberrations when only one glass type is used. Conventional designs usually use two or three glass types to correct color aberrations. The present invention performs the correction in the presence of a single material type used in all lenses due to the specific lens and mirror configuration. In very deep UV, both silica and  $\text{CaF}_2$  are highly dispersive, so even a narrow spectral  
10 bandwidth at very short wavelengths can require the correction of quite a few distinct color aberrations. Such color aberrations may include primary and secondary axial color, primary and secondary lateral color, chromatic variation of spherical aberration, and chromatic variation of coma. In the present invention, lens and mirror positioning permits primary axial and lateral color to be completely corrected. Secondary axial and lateral color cannot  
15 be completely corrected, but can be kept small enough to be acceptable over a relatively narrow spectral bandwidth. Chromatic variation of both spherical aberration and coma can also be corrected using this small fold mirror and dual field lens design. The physical separation between positive and negative axial color contributions present in the design of FIG. 3, particularly the separation to positionally disparate locations within the design, leads  
20 to special problems in correcting the chromatic variation of aberrations. Minimization of chromatic aberration variations requires a very particular arrangement of lens powers and shapes such as illustrated in FIG. 3 and later in embodiments 4-8.

The design of FIG. 3 provides an optical system having a long working distance between the optical system and the surface being inspected, particularly between the final  
25 lens in the system 308 and the surface of the object or specimen 309 (not shown) being imaged. The arrangement of FIG. 3 further provides a high numerical aperture and no central obscuration. A high numerical aperture provides for high resolution imaging and collecting as large an angular range above the surface being imaged as possible. Numerical apertures of greater than 0.8 can be achieved with excellent performance. A numerical  
30 aperture of 0.8 corresponds to collecting angles above the surface from normal to 53 degrees.

Further, unlike many catadioptric optical systems, the design of FIG. 3 has no central obscuration to block low frequency information. The FIG. 3 design does not have this problem and permits utilization of all low frequency information.

The design illustrated in FIG. 3 also provides relatively reasonable tolerances which can be more easily manufactured. The benefit of reasonable tolerances in the design of FIG. 3 is that it overcomes problems present in many known high NA, broad bandwidth systems having some optical elements with very tight position and thickness tolerances. These tight tolerances may make previous designs either too expensive or in some cases impossible to build and operate in a production environment.

FIG. 5 shows a more complex version of the design that provides additional narrow band aberration correction to give a 0.7 NA, long working distance, unobscured design using only fused silica. The object extends from 0.25 mm to 0.75 mm off axis and the design has a bandwidth of 1 nm from 192.8-193.8 nm. The surface data for an example of this type of design is listed in Table 1. Performance for the system shown in FIG. 5 is limited by chromatic variation in aberrations rather than higher order axial color. Other versions are possible and would require minimal effort by those of ordinary skill when presented with this disclosure.

As illustrated in FIG. 5, energy, such as laser energy, is transmitted from energy source 5000 (not shown) and into objective 500. Objective 500 includes lens arrangement 530, which includes a first lens pair 531 including first lens 501 and second lens 502, followed by third lens 503, fourth lens 504, and fifth lens 505. Energy is focused by lens arrangement 530 toward field lens 506, which then directs energy toward the small folding mirror or reflecting surface, here specifically first mirror 507. Energy is directed from first mirror 507 toward lens 508 and to Mangin mirror 509, which reflects light energy back through lens 508 and toward the second part of the small folding mirror or reflecting surface, specifically to second mirror 510.

In FIG. 5, light is reflected from second folding mirror 510 to field lens 533, which includes first field lens 511 and second field lens 512. From the field lens 533, light is transmitted to focusing lens arrangement 534, which includes first focusing lens 513, second focusing lens 514, third focusing lens 515, fourth focusing lens 516, fifth focusing lens 517, sixth focusing lens 518, and seventh focusing lens 519. The specimen or surface

520 to be examined is not shown in FIG. 5, but is located to the right of the objective 500 in the orientation of FIG. 5. Light energy strikes the specimen and reflects back through the objective 500 of FIG. 5. Alternately, light energy can transmit through the specimen and then through the objective 500 from right to left as shown in FIG. 5.

5 **Table 1** Surface data for the folded design of FIG. 5 operating at 193 nm wavelength with a 1 nm bandwidth

Surf	Radius	Thickness *	Material	Element Number
OBJ	Infinity	Infinity		N/S**
STO	Infinity	-32.038		N/S
2	81.983	5.000	Silica	501
3	18.305	4.216		501
4	-27.049	5.000	Silica	502
5	-61.738	33.261		502
6	1276.054	7.000	Silica	503
7	-83.831	0.500		503
8	79.482	8.000	Silica	504
9	-229.250	1.000		504
10	47.191	7.000	Silica	505
11	138.080	66.471		505
12	14.544	4.000	Silica	506
13	514.189	7.697		506
14	Infinity	0.000	Mirror	507
15	Infinity	-77.947		507
16	50.786	-8.000	Silica	508
17	139.802	-22.299		508
18	32.934	-8.000	Silica	509
19	60.774	8.000	Mirror	509
20	32.934	22.299		509
21	139.802	8.000	Silica	508
22	50.786	77.947		508
23	Infinity	0.000	Mirror	510

24	Infinity	-3.500		510
25	Infinity	-2.500		510
26	-50.929	-5.724	Silica	511
27	-41.159	-1.814		511
28	302.166	-6.000	Silica	512
29	24.557	-48.713		512
30	544.674	-6.500	Silica	513
31	89.379	-30.822		513
32	-90.727	-12.569	Silica	514
33	-64.505	-6.000		514
34	-233.637	-8.000	Silica	515
35	83.534	-0.500		515
36	-92.578	-5.679	Silica	516
37	1208.052	-0.500		516
38	-50.386	-5.8316	Silica	517
39	-146.956	-0.500		517
40	-30.274	-5.971	Silica	518
41	-56.351	-0.500		518
42	-12.744	-7.155	Silica	519
43	-12.195	-14.453		519
44	Infinity	1.68E-05		N/S
IMA	Infinity			N/S

\* Surface thickness represents the thickness of a surface when at the “upstream” side of the element or distance between the surface and the next surface if at the “downstream” side of the element. For example, surface 2 on element 501 has a radius of 81.983 millimeters and the lens is 5.000 millimeters thick. Surface 3 of lens element 501 has a radius of 18.305 millimeters and is 4.216 millimeters from the next surface, which is surface 4 on element 502.

\*\* Certain elements relating to but not critical to the design are not shown in the figures.

A fourth embodiment of the invention is presented in FIG. 6. FIG. 6 illustrates a folded 0.7 NA catadioptric objective using two materials. This design uses silica and

calcium fluoride to further increase system bandwidth. Calcium fluoride is added to the field lenses in this design make both such lenses achromats. The design of FIG. 6 is corrected for light energy from 193 to 225 nm. Surface data for a system of the fourth embodiment is presented in Table 2.

5 As shown in FIG. 6, light energy or laser energy is transmitted from energy source 6000 (not shown) and into objective 600. Objective 600 includes a lens arrangement 630, which includes first lens 601, second lens 602, third lens 603, fourth lens 604, fifth lens 605, and sixth lens 606. Energy is focused by lens arrangement 630 toward field lens arrangement 631, which includes seventh lens 607, eighth lens 608, ninth lens 609, and  
10 tenth lens 610. Eighth lens 608 and tenth lens 610 are formed of calcium fluoride (CaF<sub>2</sub>). This field lens arrangement 631 directs light energy to first small folding mirror or reflecting surface 611, which directs energy toward lens 612 and to Mangin mirror 613. Light energy reflects back from Mangin mirror 613 back through lens 612 and toward the second part of the small folding mirror or reflecting surface, specifically to second mirror  
15 614.

Light is reflected from second folding mirror 614 to second field lens arrangement 632, which includes first field lens 615, second field lens 616, and third field lens 617. Both first field lens 615 and third field lens 617 are formed of calcium fluoride. From the field lens arrangement 632, light energy is transmitted to focusing lens arrangement 633,  
20 which includes first focusing lens 618, second focusing lens 619, third focusing lens 620, fourth focusing lens 621, fifth focusing lens 622, and sixth focusing lens 623. The specimen or surface 624 to be examined is not shown in FIG. 6, but is located to the right of the objective 600 in the orientation of FIG. 6.

**Table 2** Surface data for a folded design at 193 nm with a 32 nm bandwidth

25

Surf	Radius	Thickness	Material	Element Number
OBJ	Infinity	Infinity		N/S
STO	Infinity	-32.204		N/S
2	-101.014	3.000	Silica	601
3	25.381	74.761		601
4	-29.809	5.000	Silica	602
5	-31.309	1.000		602

6	183.355	7.500	Silica	603
7	-109.361	0.500		603
8	99.287	7.000	Silica	604
9	-250.439	1.000		604
10	50.010	5.500	Silica	605
11	118.693	3.882		605
12	-216.754	4.000	Silica	606
13	127.307	44.956		606
14	28.389	24.000	Silica	607
15	7.676	0.683		607
16	12.387	3.000	CaF <sub>2</sub>	608
17	-10.095	0.475		608
18	-8.982	5.497	Silica	609
19	8.000	0.093		609
20	8.069	3.000	CaF <sub>2</sub>	610
21	-9.002	5.673		610
22	Infinity	0.000	Mirror	611
23	Infinity	-94.049		611
24	60.160	-8.000	Silica	612
25	158.201	-20.471		612
26	34.636	-8.000	Silica	613
27	65.450	8.000	Mirror	613
28	34.636	20.471		613
29	158.201	8.000	Silica	612
30	60.160	94.049		612
31	Infinity	0.000	Mirror	613
32	Infinity	-3.500		613
33	Infinity	-2.500		613
34	-26.228	-2.500	CaF <sub>2</sub>	614
35	12.608	-0.102		614
36	12.417	-9.995	Silica	615
37	-34.270	-2.110		615
38	70.277	-2.000	CaF <sub>2</sub>	616

39	25.599	-36.553		616
40	-139.138	-7.000	Silica	617
41	75.025	-63.911		617
42	-347.832	-6.000	Silica	618
43	-60.817	-6.000		618
44	-125.144	-9.000	Silica	619
45	146.610	-0.500		619
46	-69.321	-9.000	Silica	620
47	482.420	-0.500		620
48	-44.275	-10.217	Silica	621
49	-474.223	-0.500		621
50	-19.707	-10.437	Silica	622
51	-30.002	-18.250		622
52	Infinity	3.14E-05		N/S
IMA	Infinity			

It is also possible to use a diffractive optic instead of a second glass material to increase the bandwidth. In this case, the diffractive optic must be manufactured with a specific phase profile to ensure proper diffraction efficiency and angles. Such a design would be possible for those skilled in the art once presented with this disclosure.

The embodiments illustrated in FIGS. 5 and 6 have two disadvantages. First, the optical axis of the Mangin mirror image relay is at 90 degrees to the optical axis defined by the focusing lenses. This arrangement can mandate very high angular and position tolerances for the optical elements in the Mangin mirror image relay. This can result in manufacturing difficulties and increased system cost. For this reason, it is desirable to have a minimum number of lens elements in this 90 degree path. Thus, the 90 degree optical axis can limit the design options for this objective. Second, the pupil plane for aperturing and Fourier filtering is located in a noncollimated region inside the objective. This can produce problems when introducing apertures and filters. Also, because the pupil plane is in a noncollimated region, it is not at the Fourier plane of the object being inspected. This can significantly reduce the effectiveness of Fourier filtering.



The fifth embodiment, illustrated in FIG. 7, solves the problems of the 90 degree bend issue with respect to the Mangin mirror image relay and the internal pupil plane. FIG. 7 illustrates an in-line or straight 0.7 NA catadioptric objective employing a single glass material. The arrangement of FIG. 7 also allows for improved design performance and relaxes manufacturing tolerances. For example, the decentering of any lens element by 5 microns will cause less than one quarter wave of coma without using any compensation elements. Using element decenters and tilts as compensation elements, the tolerances become even more relaxed. The arrangement of FIG. 7 includes one bend with some lenses after the second internal image. These lenses have extremely relaxed tolerances and tend not to affect the manufacturability of the system. The arrangement of FIG. 7 also has an external pupil plane 701 for aperturing and Fourier filtering. This pupil plane is in the collimated region so it corresponds to the Fourier plane of the object. The object in the arrangement of FIG. 7 extends from 0.25 mm to 0.75 mm off axis and the design has a bandwidth of 1 nm from 192.8-193.8 nm.

As shown in FIG. 7, light energy or laser energy is transmitted from energy source 7000 (not shown) into objective 700. Objective 700 includes first lens 702 and first field lens 703. This first field lens 703 directs light energy to small folding mirror or reflecting surface 704, which directs energy toward focusing lenses 705 and 706 and to Mangin mirror 707. Light energy reflects back from Mangin mirror 707 back through focusing lenses 706 and 705 and past small folding mirror or reflecting surface 704. Light energy then passes through second field lens 708 and through focusing lens arrangement 720, which includes first focusing lens 709, second focusing lens 710, third focusing lens 711, fourth focusing lens 712, fifth focusing lens 713, sixth focusing lens 714, and seventh focusing lens 715. The specimen or surface 716 to be examined is not shown in FIG. 7, but is located to the right of the objective 700 in the orientation shown in FIG. 7. Light energy strikes the specimen 717 and reflects back through the objective 700 of FIG. 7. Surface data for a system employing the design of FIG. 7 is listed in Table 3.

In a darkfield arrangement, light energy is directed toward the specimen surface as shown in FIG. 2. Light energy may scatter toward the objective, i.e. toward seventh focusing lens 515 in the design of FIG. 7. In such an arrangement, light energy passes back through the system, striking the Mangin mirror 707 and passing through first lens 702.

The design of FIG. 7 provides an optical system with an external pupil plane 701 to support aperturing and Fourier filtering. An aperture can be used in connection with the FIG. 7 design to provide control of the numerical aperture of the imaging system. Such an aperture may optionally be placed at the pupil plane thereby permitting control of overall resolution and depth of focus. Fourier filtering is particularly useful in applications such as laser dark field imaging. Fourier filtering permits filtering surface patterns which repeat by increasing the signal-to-noise ratio for defects on the surface.

**Table 3** Surface data for linear design shown in FIG. 7 at 193 nm with a 1 nm bandwidth

Surf	Radius	Thickness	Material	Element Number
OBJ	Infinity	Infinity		N/S
STO	Infinity	25.000		701
2	-222.386	4.000	Silica	702
3	-28.670	40.503		702
4	39.160	2.500	Silica	703
5	177.023	10.000	Silica	703
6	Infinity	0.000	Mirror	704
7	Infinity	-98.015		704
8	-320.423	-6.000	Silica	705
9	149.893	-142.852		705
10	58.250	-8.000	Silica	706
11	210.014	-20.290		706
12	41.193	-9.000	Silica	707
13	81.848	9.000	Mirror	707
14	41.193	20.290		707
15	210.014	8.000	Silica	706
16	58.250	142.852		706
17	149.893	6.000	Silica	705
18	-320.423	98.015		705
19	Infinity	44.416		705
20	70.917	15.000	Silica	708

21	48.487	83.467		708
22	326.205	11.000	Silica	709
23	-86.355	83.991		709
24	235.491	9.000	Silica	710
25	-111.089	10.357		710
26	-58.901	4.000	Silica	711
27	-3728.698	89.493		711
28	45.959	6.365	Silica	712
29	41.432	9.332		712
30	-739.118	6.000	Silica	713
31	-79.014	1.000		713
32	44.790	9.000	Silica	714
33	182.972	1.000		714
34	22.072	20.822	Silica	715
35	36.911	11.529		715
IMA	Infinity			N/S

The sixth embodiment presented in FIG. 8 is similar to the fifth embodiment of FIG. 7, but has been optimized for a wavelength of 157 nm. The change in wavelength requires changing the material used from fused silica to calcium fluoride. The index of fused silica at a wavelength of 193 nm is nearly identical to the index for calcium fluoride at 157 nm, so the design requires no major changes aside from the material. However, the dispersion of calcium fluoride at 157 nm is larger than the dispersion of fused silica at 193 nm, which may require some minor changes to further optimize the design. The design presented in FIG. 8 also provides the option of splitting the Mangin mirror into a front surface mirror and a meniscus lens, which can in some cases simplify manufacturing. This split Mangin mirror approach can be employed on the other catadioptric objective designs of FIGS. 3-9 as well. The object extends from 0.25 mm to 0.75 mm off axis and the design has a bandwidth of 0.5 nm from 156.75-157.25 nm.

As shown in FIG. 8, light energy or laser energy is transmitted from energy source 8000 (not shown) and into objective 800. This objective 800 also has an external pupil plane 801 as in the design presented in FIG. 7. Objective 800 includes first lens 802 and first field lens 803. This first field lens 803 directs light energy to small folding mirror or reflecting surface 804, which directs energy toward focusing lenses 805, 806, and 807 and

to mirror surface 808. Light energy reflects back from mirror surface 808 back through focusing lenses 807, 806, and 805 and past small folding mirror or reflecting surface 804. Light energy then passes through second field lens group 820 which includes first field lens 809, second field lens 810, and third field lens 811. Light then passes through focusing lens arrangement 821, which includes first focusing lens 812, second focusing lens 813, third focusing lens 814, fourth focusing lens 815, fifth focusing lens 816. The specimen or surface 817 to be examined is not shown in FIG. 8, but is located to the right of the objective 800 in the orientation shown in FIG. 8. Light energy strikes the specimen 817 and reflects back through the objective 800 of FIG. 8. Light from specimen 817 can be apertured or Fourier filtered at pupil plane 801 as described in the fifth embodiment and presented in FIG. 7.

The surface data for a system having the objective shown in FIG. 8 is listed in Table 4.

**Table 4** Surface data for a linear design as shown in FIG. 8 at 157 nm with a 0.5 nm bandwidth

Surf	Radius	Thickness	Material	Element Number
OBJ	Infinity	Infinity		N/S
STO	Infinity	25.000		801
2	-228.090	4.000	CaF <sub>2</sub>	802
3	-26.271	34.743		802
4	27.340	2.500	CaF <sub>2</sub>	803
5	78.838	10.000		803
6	Infinity	0	Mirror	804
7	Infinity	-75.368		804
8	332.074	-6.000	CaF <sub>2</sub>	805
9	75.615	-84.484		805
10	53.058	-7.000	CaF <sub>2</sub>	806
11	129.105	-12.000		806
12	40.981	-7.000	CaF <sub>2</sub>	807
13	128.091	-7.480		807
14	69.614	7.480	Mirror	808

15	128.091	7.000	CaF <sub>2</sub>	807
16	40.981	12.000		807
17	129.105	7.000	CaF <sub>2</sub>	806
18	53.058	84.484		806
19	75.615	6.000	CaF <sub>2</sub>	805
20	332.074	75.368		805
21	Infinity	39.173		
22	24.018	15.000	CaF <sub>2</sub>	809
23	26.501	24.354		809
24	-15.238	13.419	CaF <sub>2</sub>	810
25	-26.901	1.000		810
26	355.973	7.000	CaF <sub>2</sub>	811
27	-56.508	110.232		811
28	58.858	10.000	CaF <sub>2</sub>	812
29	1338.307	6.0469		812
30	-54.890	10.000	CaF <sub>2</sub>	813
31	-72.556	26.319		813
32	-308.917	6.500	CaF <sub>2</sub>	814
33	-95.467	1.000		814
34	34.0794	8.000	CaF <sub>2</sub>	815
35	110.300	1.000		815
36	16.407	9.697	CaF <sub>2</sub>	816
37	29.683	11.927		816
IMA	Infinity			

The seventh embodiment illustrated in FIG. 9 has similarities to the fifth and sixth embodiments presented in FIGS. 7 and 8. The design presented in FIG. 9 uses the straight through 0.7 NA catadioptric approach to allow more design flexibility, improve performance, and relax the manufacturing tolerances. In addition, similar to the design of FIG. 6, a second glass material, calcium fluoride, is used to increase the correction bandwidth. The design of FIG. 9 is corrected from 193 to 203 nm. The FIG. 9 design has one calcium fluoride element in the eyepiece group and one calcium fluoride/silica doublet near the intermediate image. The object extends from 0.25 mm to 0.75 mm off axis and the design has a bandwidth from 193.3-203.3 nm.

As shown in FIG. 9, light energy or laser energy is transmitted from energy source 9000 (not shown) and into objective 900. As in objective embodiments presented in FIG 7 and FIG 8, an external pupil plane 901 is available for aperturing and fourier filtering. Objective 900 includes first lens 902 and first field lens arrangement 930, which includes  
 5 first field lens 903 and second field lens 904. This first field lens arrangement 930 directs light energy to small folding mirror or reflecting surface 905, which reflects energy toward focusing lenses 906 and 907 and to Mangin mirror 908. Light energy reflects back from Mangin mirror 908 back through focusing lenses 907 and 906, and past small folding mirror or reflecting surface 905. Light energy then passes through second field lens arrangement  
 10 931, which includes third field lens 909, fourth field lens 910, and fifth field lens 911. Light then passes through focusing lens arrangement 932, which includes first focusing lens 912, second focusing lens 913, third focusing lens 914, fourth focusing lens 915, fifth focusing lens 916, sixth focusing lens 917, seventh focusing lens 918. The specimen or surface 919 to be examined is not shown in FIG. 9, but is located to the right of the objective 900 in the  
 15 orientation shown in FIG. 9. Light energy strikes the specimen 917 and reflects back through the objective 900 of FIG. 9.

The surface data for the design of FIG. 9 is listed in Table 5.

**Table 5** Surface data for a linear design as in FIG. 9 at 193 nm with a 10 nm bandwidth

Surf	Radius	Thickness	Material	Element Number
OBJ	Infinity	Infinity		N/S
STO	Infinity	35.063		901
2	527.763	4.000	Silica	902
3	-32.542	8.204		902
4	572.044	2.000	Silica	903
5	16.118	1.447		903
6	17.545	5.000	CaF2	904
7	-65.290	35.838		904
8	Infinity	0.000	Mirror	905
9	Infinity	-96.873		905
10	-795.110	-10.000	Silica	906

11	92.663	-199.957		906
12	64.768	-8.000	Silica	907
13	281.874	-14.019		907
14	38.871	-9.000	Silica	908
15	80.841	9.000	Mirror	908
16	38.871	14.019		908
17	281.874	8.000	Silica	907
18	64.768	199.957		907
19	92.663	10.000	Silica	906
20	-795.110	96.873		906
21	Infinity	9.399		906
22	-16.045	2.000	Silica	909
23	24.034	0.217		909
24	24.751	4.000	CaF2	910
25	-16.515	22.166		910
26	38.990	4.000	Silica	911
27	41.231	164.091		911
28	1232.004	10.000	Silica	9121
29	-95.859	1.000		912
30	79.148	9.000	Silica	913
31	-1367.718	33.541		913
32	-59.580	4.000	Silica	914
33	201.391	45.680		914
34	173.228	4.500	Silica	915
35	58.668	7.500		915
36	-127.932	6.000	Silica	916
37	-41.246	1.000		916
38	31.082	9.000	Silica	917
39	153.068	1.000		917
40	17.627	12.491	Silica	918
41	35.390	11.566		918
IMA	Infinity			

A complete imaging system, such as described in embodiments 1-2 and presented in FIGS. 1-2, requires an objective, such as described in embodiments 3-6 and presented in FIGS. 3-9, and image forming optics. The image forming optics can employ different designs. The image forming optics can be a static tube lens capable of producing a single magnification. In a static tube lens arrangement, different magnifications are achieved by using different tube lenses, which may be readily designed by one skilled in the art. Another image forming optic design is a zooming tube lens. A zooming tube lens requires only a single optical system to produce a wide range of magnifications. Examples of two different types of zooming tube lenses are presented in embodiments 7 and 8 below. Image forming optics must be corrected for the wavelength and spectral bandwidth of the illumination source.

The seventh embodiment illustrated in FIG. 10 is an image forming tube lens employing a varifocal two motion zoom to change magnifications. The design methodology is similar to that presented in the United States Patent Application 08/908,247, entitled "Ultra-Broadband UV Microscope Imaging System with Wide Range Zoom Capability," filed on August 7, 1997, of which this invention is a continuation in part. The design consists of a stationary doublet 1020, a zooming group 1021, and a detector group 1022. The stationary doublet includes a first doublet lens 1002 and a second doublet lens 1003. The zooming group consists of a first zoom lens 1004, a second zoom lens 1005, and a third zoom lens 1006. The detector group 1022 consists of a protective window 1007 and a detector 1008. Different magnifications are achieved by moving the zoom group along the optical axis and then repositioning the detector with the protective window to refocus. Three example magnifications are shown in FIG. 11. The low magnification zoom position 1101 has the shortest total length with the zoom group 1121 farthest away from the doublet 1120. For medium magnification 1102 the total length from the doublet 1120 to the detector group 1122 increases and the distance from the doublet 1120 to the zoom group 1121 decreases. For high magnification 1103 the maximum distance from the doublet 1120 to the detector group 1122 is achieved and the distance from the doublet 1120 to the zoom group 1121 is minimized. This design is capable of magnifications from 38 times to greater than 152 times. Over the magnification range from 38 times to 152 times, the total length of the system from the doublet 1020 to the detector 1008 changes from 320 mm to 880 mm. The three lenses that move in the zooming group 1021 are moved a total of 68 mm. The pupil 1201 of the design in FIG. 12 is matched to the design presented in FIG. 7. One



skilled in the art, when presented with this disclosure, could readily design a similar tube lens for use with the objective designs presented in FIGS. 3-9 as well as other designs that are within the scope of this invention. It is also possible for someone skilled in the art, when presented with this disclosure, to design a varifocal two motion zoom with other magnifications and magnification ranges.

The surface data for the design of FIG. 10 is listed in Table 6.

**Table 6** Surface data for an image forming tube lens as in FIG. 110 at 193 nm with a 1.5 nm bandwidth

Surf	Radius	Thickness	Glass	Surface number
OBJ	Infinity	Infinity		N/S
STO	Infinity	20.000		1001
2	121.600	3.000	Caf2	1002
3	-77.915	0.500		1002
4	-78.860	2.000	Silica	1003
5	-1820.981	90.732		1003
6	106.439	2.500	Caf2	1004
7	59.162	99.528		1004
8	50.266	4.000	Silica	1005
9	124.701	14.006		1005
10	-687.986	3.000	Caf2	1006
11	53.069	470.445		1006
12	Infinity	1.000	Silica	1007
13	Infinity	1.000		1007
IMA	Infinity			1008

The eighth embodiment illustrated in FIG. 12 is an image forming tube lens using an optically compensated single motion zoom to change magnifications. The design methodology is similar to that in a paper by David R. Shafer, "Catadioptric optically compensated zooming system with one moving element" Proc SPIE Vol. 2539, pp. 235-240. The design consists of a first doublet 1220, a zooming group 1221, a mirror 1206, a second doublet 1222, and a detector 1210. The first doublet consists of a doublet lens 1202

and a following doublet lens 1203. The zooming group consists of a first zoom lens 1204 and a second zoom lens 1205. Different magnifications are achieved by moving the zoom group 1221 along the optical axis of the first doublet 1220, the zoom group 1221, and the mirror 1206. No other motion is required.

- 5 Three example magnifications are shown in FIG. 13. The low magnification zoom position 1301 has the zoom group 1321 very close to the first doublet 1320. For the medium magnification 1302, the zoom group is in between the first doublet 1320 and the mirror 1304. For the high magnification 1303 the zoom group 1321 is relatively close to the mirror 1304. The design is capable of magnifications from 60 times to greater than 180  
10 times.

The pupil 1201 of the design in FIG. 12 is matched to the design presented in FIG. 7. The surface data for the design of FIG. 12 is listed in Table 7.

**Table 7** Surface data for an image forming tube lens as in FIG. 12 at 193 nm with a 1.5 nm bandwidth

15

Surf	Radius	Thickness	Glass	Surface number
OBJ	Infinity	Infinity		N/S
STO	Infinity	20.000		1201
2	-	0.000	-	N/S
3	123.897	8.000	caf2	1202
4	-213.430	33.518		1202
5	-119.986	4.000	silica	1203
6	206.676	315.675		1203
7	24267.100	4.000	caf2	1204
8	117.959	10.577		1204
9	125.844	5.000	silica	1205
10	325.138	319.238		1205
11	-1125.668	-319.238	MIRROR	1206
12	325.138	-5.000	silica	1205
13	125.844	-10.577		1205
14	117.959	-4.000	caf2	1204

15	24267.100	-305.678		1204
16	-	0.000	-	N/S
17	Infinity	0.000	MIRROR	1207
18	-	0.000	-	N/S
19	Infinity	36.000		N/S
20	39.403	6.000	silica	1208
21	81.584	0.500		1208
22	50.614	4.000	silica	1209
23	33.375	11.140		1209
IMA	Infinity			1210

While the invention has been described in connection with specific embodiments thereof, it will be understood that the invention is capable of further modifications. This application is intended to cover any variations, uses or adaptations of the invention following, in general, the principles of the invention, and including such departures from the present disclosure as come within known and customary practice within the art to which the invention pertains.

**WHAT IS CLAIMED IS:**

1. A combined catadioptric lensing and mirror optical inspection system comprising:
  - a primary focusing lens arrangement;
  - a primary field lens arrangement;
  - 5 a fold mirror;
  - a Mangin mirror arrangement;
  - a secondary field lens arrangement; and
  - a secondary focusing lens arrangement;wherein said system is able to received transmitted light energy and pass light  
10 energy to said primary focusing lens arrangement, said primary field lens arrangement, said fold mirror, said Mangin mirror arrangement, said secondary field lens arrangement, and said secondary focusing lens arrangement;  
  
and further wherein said combined catadioptric lensing and mirror optical inspection system has off-axis orientation whereby output rays provided by said Mangin mirror  
15 arrangement are physically displaced from output rays transmitted toward said Mangin mirror arrangement.
2. The system of claim 1, further comprising a second fold mirror which may receive energy from said Mangin mirror arrangement and pass energy to said secondary field lens arrangement.
- 20 3. The system of claim 1, wherein said primary focusing lens arrangement comprises at least one lens, said primary field lens arrangement comprises at least one lens, said secondary field lens arrangement comprises at least one lens, said secondary focusing lens arrangement comprises at least one lens, and wherein all lenses in the system are constructed using a single material.
- 25 4. The system of claim 3, wherein said single glass material comprises one from the group of:
  - fused silica; and
  - calcium fluoride.
5. The system of claim 1, wherein said fold mirror folds light energy at an angle  
30 greater than 45 degrees.

6. The system of claim 1, wherein said system provides a working distance greater than six millimeters.
7. The system of claim 1, wherein said system provides a numerical aperture in excess of .7.
- 5 8. The system of claim 1, wherein said system has an accessible pupil plane and further comprising at least one from the group of:
- a Fourier filter; and
  - an aperture.
9. The system of claim 1, wherein the system is free of internal beamsplitters.
- 10 10. The system of claim 1, wherein light energy is imparted to said system by one from the group of:
- an unnarrowed excimer laser;
  - a lamp having a bandpass filter;
  - a frequency converted laser; and
  - 15 a deuterium laser.
11. The system of claim 1, further comprising:
- an illumination source for producing said light energy;
  - image forming optics; and
  - a detector.
- 20 12. A method for inspecting a specimen, comprising the steps of:
- folding received light energy off a folding mirror, thereby providing a first image;
  - imparting light energy to a Mangin mirror; and
  - directing light energy from said Mangin mirror through a second lensing arrangement, whereby light energy directed from said Mangin mirror forms a second image
  - 25 displaced from said first image.
13. The method of claim 12, further comprising the steps of:
- receiving light energy from a light energy source; and
  - imparting light energy from said light energy source through a first lensing arrangement, a field lensing arrangement, and to said folding mirror.
- 30 14. The method of claim 12, further comprising the step of:

passing light energy to image forming optics and subsequently to a detector after said directing step.

15. The method of claim 12, further comprising separating elements used in connection with said method from said specimen by at least six millimeters.

5 16. The method of claim 12, further comprising the step of fourier filtering energy received from said directing step.

17. The method of claim 12, wherein said method uses a plurality of lenses and said lenses are fashioned from a single material.

18. The method of claim 12, further comprising passing said light energy to a second  
10 folding mirror subsequent to said directing step.

19. An objective for inspecting a specimen, comprising:

a fold mirror for folding received energy, said field mirror providing input rays having a predetermined orientation; and

a refractive lens/mirror element, wherein said refractive lens/mirror element  
15 provides output rays having an orientation displaced from said predetermined orientation.

20. The objective of claim 19, further comprising:

a primary focusing lens arrangement;

a primary field lens arrangement;

a secondary field lens arrangement; and

20 a secondary focusing lens arrangement.

21. The objective of claim 20, wherein transmitted energy to said objective may pass sequentially to said primary focusing lens arrangement, said primary field lens arrangement, said fold mirror, said refractive lens/mirror element, said secondary field lens arrangement, and said secondary focusing lens arrangement.

25 22. The objective of claim 19, further comprising a second fold mirror which may receive energy from said refractive lens/mirror arrangement and pass energy to said secondary field lens arrangement.

23. The objective of claim 20, wherein said primary focusing lens arrangement comprises at least one lens, said primary field lens arrangement comprises at least one lens,  
30 said secondary field lens arrangement comprises at least one lens, said secondary focusing

lens arrangement comprises at least one lens, and wherein all lenses in the system are constructed using a single material.

24. The objective of claim 23, wherein said single glass material comprises one from the group of:

- 5           fused silica; and  
          calcium fluoride.

25. The objective of claim 19, wherein said objective provides a numerical aperture in excess of .7.

26. The objective of claim 19, wherein said objective is free of internal beamsplitters.

10   27. The objective of claim 19, wherein light energy is imparted to said objective by one from the group of:

- an unnarowed excimer laser;  
          a lamp having a bandpass filter;  
          a frequency converted laser; and  
15       a deuterium laser.

28. An apparatus for inspecting a specimen, comprising:

          means for folding received light energy off a folding mirror, thereby providing a first image;

          means for imparting light energy to a refractive lens/mirror element; and

20       means for directing light energy from said refractive lens/mirror arrangement through a lensing arrangement, whereby light energy directed from said lens/mirror arrangement forms a second image displaced from said first image.

29. The apparatus of claim 28, further comprising:

- first means for focusing;  
25       a primary field lens arrangement;  
          a secondary field lens arrangement; and  
          second means for focusing.

30. The apparatus of claim 29, wherein transmitted energy to said apparatus may pass sequentially to said first focusing means, said primary field lens arrangement, said fold

mirror, said refractive lens/mirror element, said secondary field lens arrangement, and said second focusing means.

31. The apparatus of claim 28, further comprising a second fold mirror which may receive energy from said refractive lens/mirror arrangement and pass energy to said secondary field lens arrangement.

32. The apparatus of claim 28, wherein said first focusing means comprises at least one lens, said primary field lens arrangement comprises at least one lens, said secondary field lens arrangement comprises at least one lens, said second focusing means comprises at least one lens, and wherein all lenses in the system are constructed using a single material.

33. The apparatus of claim 32, wherein said single glass material comprises one from the group of:

fused silica; and  
calcium fluoride.

34. The apparatus of claim 28, wherein said objective provides a numerical aperture in excess of .7.

35. The apparatus of claim 28, wherein said apparatus is free of internal beamsplitters.

36. The apparatus of claim 28, wherein light energy is imparted to said apparatus by one from the group of:

an unnarrowed excimer laser;  
a lamp having a bandpass filter;  
a frequency converted laser; and  
a deuterium laser.

37. An apparatus for imaging a specimen comprising:

an illumination system;  
an unobscured catadioptric objective;  
image forming optics; and  
a detector.

38. The apparatus of claim 37, wherein said illumination system has a central wavelength and a spectral bandwidth, and wherein the catadioptric objective and the image forming optics are correlated with the central wavelength and spectral bandwidth of the illumination.



39. The apparatus of claim 38 where the illumination central wavelength is at most 365 nm.

40. The apparatus of claim 37, wherein the specimen comprises one from a group comprising:

- 5           a photomask; and  
          a semiconductor wafer.

41. The apparatus of claim 40 where the illumination system employs illumination of at least one from a group comprising:

- transmitted light illumination; and  
10          reflected light illumination;  
          and wherein transmitted light illumination is employed when said specimen comprises a photomask.

42. The apparatus of claim 41 wherein the illumination system uses at least one from a group including:

- 15          bright field imaging; and  
          ring dark field imaging.

43. The apparatus of claim 41 where the illumination system comprises at least one from a group comprising:

- an excimer laser;  
20          an excimer lamp;  
          an argon laser;  
          an arc lamp;  
          a deuterium lamp;  
          a hollow cathode lamp;  
25          a metal halide lamp;  
          a solid state laser;  
          a frequency converted solid state laser; and  
          a frequency up-converted laser.

44. The apparatus of claim 37, wherein bandwidth of the illumination system is  
30 narrowed using at least one from a group comprising:

- an optical bandpass filter;

an optical interference filter;  
a prism;  
a grating; and  
a diffractive optic.

- 5 45. The apparatus of claim 37, further comprising a condenser objective to collect light transmitted from said illumination system and focus said light to an area nominally sized to a predetermined imaged area.
46. The apparatus of claim 37, wherein said image forming optics comprise a plurality of lenses fashioned from a single glass material.
- 10 47. The apparatus of claim 46, wherein the single glass material comprises one from a group comprising:  
silica; and  
calcium fluoride.
48. The apparatus of claim 37, wherein said image forming optics comprises a plurality  
15 of lenses fashioned from two glass materials.
49. The apparatus of claim 37, wherein said image forming optics comprises:  
a plurality of lenses fashioned from one glass material; and  
at least one diffractive surface.
50. A catadioptric imaging system for inspecting a specimen comprising:  
20 an unobscured catadioptric objective; and  
image forming optics;  
wherein the catadioptric objective of said system is corrected to operate over a bandwidth greater than or equal to approximately of 0.3 nm.
51. The system of claim 50 wherein said image forming optics are separated from said  
25 specimen by greater than or equal to 6 millimeters.
52. The system of claim 50 wherein the image forming optics comprise a plurality of lenses fashioned from a single material.
53. The system of claim 52 wherein the single material comprises one from the group  
of:  
30 silica; and  
calcium fluoride.

54. The system of claim 50 wherein the image forming optics comprise a plurality of lenses fashioned from one from the group comprising:

two glass materials; and

one glass material and one or more diffractive surfaces.

5 55. The system of claim 54 where the glass materials are one or more from the group of:  
silica; and  
calcium fluoride.

56. The system of claim 50 wherein the system is corrected over a bandwidth of greater than or equal to approximately 10 nm.

10 57. The system of claim 50 wherein the system has a numerical aperture greater than or equal to approximately 0.4.

58. The system of claim 50 wherein the image forming optics comprise a single motion optically compensated zoom to obtain a range of magnifications.

59. An unobscured catadioptric objective comprising:

15 a primary focusing lens arrangement;

a primary field lens arrangement;

a mangin lens/mirror element;

multiple plane reflecting surfaces;

a secondary field lens arrangement; and

20 a secondary focusing lens arrangement;

wherein said combined catadioptric lensing and mirror system has an off axis orientation whereby output rays provided by said mangin mirror arrangement are physically displaced from output rays transmitted toward said mangin mirror element.

60. The system of claim 59 wherein said primary focusing lens arrangement comprises  
25 at least one lens, said primary field lens arrangement comprises at least one lens, and said secondary focusing lens arrangement comprises at least one lens.

61. The system of claim 59 wherein system chromatic correction central wavelength is less than or equal to approximately 365 nm.

62. The system of claim 59 where all system lenses are constructed of a single glass  
30 material.

63. The system of claim 59 wherein said multiple plane reflecting surfaces fold light at an angle of at least 45 degrees.

64. The system of claim 59 wherein the system is free of internal beamsplitters.

65. The system of claim 59 wherein all lenses in said system are fashioned from a group  
5 comprising:

two glass materials; and

one glass material and at least one diffractive surfaces.

66. An unobscured catadioptric objective comprising:

a primary focusing lens arrangement;

10 a primary field lens arrangement;

a Mangin lens/mirror element;

one plane reflecting surface;

a secondary field lens arrangement; and

a secondary focusing lens arrangement;

15 wherein said combined catadioptric lensing and mirror system has an off axis orientation whereby output rays provided by said Mangin mirror arrangement are physically displaced from output rays transmitted toward said mangin mirror element.

67. The system of claim 66, wherein:

said primary focusing lens arrangement comprises at least one lens;

20 said primary field lens arrangement comprises at least one lens; and

said secondary focusing lens arrangement comprises at least one lens.

68. The system of claim 66 wherein the system has a chromatic correction central wavelength of at most approximately 365 nm.

69. The system of claim 66 wherein all lenses within the system are constructed of a  
25 single glass material.

1/9

FIG. 1





FIG. 2



2/9




FIG. 3




FIG. 4




FIG. 5






FIG. 6



5/9






FIG. 9

7/9





FIG. 11









FIG. 13



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/17121

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G02B17/08 G02B21/04

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ, EPO-Internal, INSPEC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y A	DE 108 181 C (SCHUPMANN L) 22 January 1900 (1900-01-22) figure 8	12, 19, 28, 37, 50 1, 59, 66 2-11, 13-18, 20-27, 29-36, 38-49, 51-58, 60-65, 67-69
X A	GB 2 269 024 A (UNIV NOTTINGHAM) 26 January 1994 (1994-01-26) figures	19, 37, 50  1-18, 20-36, 51-69
	-/-	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

31 October 2000

Date of mailing of the international search report

08/11/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Ward, S

## INTERNATIONAL SEARCH REPORT

Internat I Application No

PCT/US 00/17121

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	EP 0 798 585 A (HUGHES AIRCRAFT CO) 1 October 1997 (1997-10-01) figures 1-7	19,37,50  1-18, 20-36, 51-69
Y A	US 3 237 515 A (ALTMAN RICHARD M) 1 March 1966 (1966-03-01) column 4, line 74 - line 75  column 5, line 1 - line 7 figures	1,59,66  2-58, 60-65, 67-69
A	US 5 717 518 A (CHUANG YUNG-HO ET AL) 10 February 1998 (1998-02-10) cited in the application abstract; figures	1-69
A	WO 99 08134 A (KLA TENCOR INC) 18 February 1999 (1999-02-18) cited in the application abstract; figures	1-69
A	US 5 140 459 A (SAGAN STEPHEN F) 18 August 1992 (1992-08-18) figures 4A,4B	1-69
A	US 4 779 966 A (FRIEDMAN IRWIN) 25 October 1988 (1988-10-25) figures	1-69
A	US 5 636 066 A (TAKAHASHI TOMOWAKI) 3 June 1997 (1997-06-03) column 39, line 52 - line 67 column 40, line 1 - line 67 column 49, line 19 - line 25 figure 29	1-69

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/17121

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 108181	C	NONE	
GB 2269024	A	26-01-1994	NONE
EP 0798585	A	01-10-1997	US 5748365 A 05-05-1998 CA 2198952 A 26-09-1997 JP 2866359 B 08-03-1999 JP 10031158 A 03-02-1998
US 3237515	A	01-03-1966	NONE
US 5717518	A	10-02-1998	DE 19731291 A 29-01-1998 GB 2315562 A 04-02-1998 JP 10177139 A 30-06-1998 US 5956174 A 21-09-1999 US 6064517 A 16-05-2000 US 5999310 A 07-12-1999 US 6133576 A 17-10-2000
WO 9908134	A	18-02-1999	US 5999310 A 07-12-1999 AU 9016798 A 01-03-1999 EP 1000371 A 17-05-2000 US 6064517 A 16-05-2000
US 5140459	A	18-08-1992	NONE
US 4779966	A	25-10-1988	NONE
US 5636066	A	03-06-1997	JP 6265789 A 22-09-1994 JP 6349699 A 22-12-1994